

FORK LENGTH (MAX.)	593.7mm
RECOMENDED FORK OFFSET	44mm
SHOCK LENGTH (EYE - EYE)	205mm
SHOCK STROKE	65mm
SHOCK HARDWARE (LOWER EYELET)	30mm x 8mm
HEAD TUBE DIAMETER UPPER	44mm
HEAD TUBE DIAMETER LOWER	55.95mm
S.H.I.S.	ZS44/28.6 ZS56/40
REAR DROPOUT SPACING (O.L.D.)	148mm
REAR AXLE SPECIFICATION	L 180mm / TL 20mm / TP M12 x 1.75
BOTTOM BRACKET	73mm BSA Threaded
CHAIN LINE	52mm
MAX. CHAIN RING (PER FRAME SIZE)	S: 30T M: 34T L: 36T XL: 38T
CHAIN LENGTH (NO. OF LINKS PER FRAME SIZE)	S: 130 M: 132 L: 134 XL: 136
SEAT POST DIAMETER	31.6mm
MAX. SEAT POST INSERTION (PER FRAME SIZE)	S: 220mm M: 240mm L: 270mm XL: 310mm
SEAT CLAMP DIAMETER	34.9mm (Included)
BRAKE MOUNT	180mm Post Mount
ISCG 05	Lower Tabs Only
RECOMMENDED TIRE SIZE	29 x 2.4
MAX. TIRE SIZE	29 x 2.6
MAIN PIVOT BEARINGS	6904 Max (20mm x 37mm x 9mm) QTY: 2
LINKAGE PIVOT BEARINGS - REAR TRIANGLE	3802 Max (15mm x 24mm x 7mm) QTY: 2
LINKAGE PIVOT BEARINGS - FRONT TRIANGLE	6902 Max (15mm x 28mm x 7mm) QTY: 2
TRUNION MOUNT BEARINGS	6901 Max (12mm x 24mm x 6mm) QTY: 2
ROCKER LINK BEARING	3208 LLU Max (15mmx24mmx7mm) QTY: 2
IDLER PULLEY BEARING	6902 ABEC 5 (15mm x 28mm x 7mm) QTY: 1