

|   |   |
|---|---|
| FORK LENGTH (MAX.)                        | 571mm   |
| RECOMENDED FORK OFFSET                    | 44mm  |
| SHOCK LENGTH (EYE - EYE)                  | 210mm   |
| SHOCK STROKE                              | 55mm  |
| SHOCK HARDWARE (BOTH ENDS)                | 30mm x 8mm  |
| HEAD TUBE DIAMETER UPPER                  | 44mm  |
| HEAD TUBE DIAMETER LOWER                  | 55.95mm   |
| S.H.I.S.                                  | ZS44/28.6 ZS56/40   |
| REAR DROPOUT SPACING (O.L.D.)             | 148mm   |
| REAR AXLE SPECIFICATION                   | L 180mm / TL 13mm / TP M12 x 1.75   |
| BOTTOM BRACKET                            | 73mm BSA Threaded   |
| CHAIN LINE                                | 52mm  |
| MAX. CHAIN RING (PER FRAME SIZE)          | S: 32T M: 34T L: 36T XL: 38T *S:30T MAX With Eagle or 55mm Chainline                          |
| SEAT POST DIAMETER                        | 31.6mm  |
| MAX. SEAT POST INSERTION (PER FRAME SIZE) | S: 220mm M: 240mm L:270mm XL: 310mm   |
| SEAT CLAMP DIAMETER                       | 34.9mm (Included)   |
| BRAKE MOUNT                               | 180mm Post Mount  |
| ISCG 05                                   | Lower Tabs Only   |
| RECOMMENDED TIRE SIZE                     | 29 x 2.4  |
| MAX. TIRE SIZE                            | 29" Tire = 2.4" (57mm at widest tread point)   27.5" Tire = 2.6" (66mm at widest tread point) |
| MAIN PIVOT BEARING                        | 6904 Max (20mm x 37mm x 9mm) QTY: 2   |
| LINKAGE PIVOT BEARING                     | 6902 Max (15mm x 28mm x 7mm) QTY: 4   |
| ROCKER LINK BEARING                       | 3802 Max (15mm x 24mm x 7mm) QTY: 2   |
| IDLER PULLEY BEARING                      | 6902 ABEC 5 (15mm x 28mm x 7mm) QTY: 1  |